

DID Series

Modules



DID2

Integrator Module

The DID2 Integrator Module improves on every major metric by which quality lighting is judged. In addition, modularity has been taken a step further to provide field changeable optics and accessories. The DID2 also includes an integrated power system for simplified installation and maintenance as well as expansive compatibility with existing DMF housings and trims and most TRIAC/ELV and controls systems.

DID4

Adjustable Integrator Module

The adjustable DID4 offers ultimate lighting flexibility to custom integrators thanks to its tool-free aiming. With full 360° directional lighting and class-leading 45° tilt, the DID4 covers angled ceilings, distant aiming and more. Combined with an integrated driver and field changeable optics and accessories, the DID4 radically simplifies modern lighting design.

THE DMF PROMISE

10-Years. Guaranteed. | Dimming Compatibility. Universal. | Tech Support. Direct.



	<div> <div>DID2</div> <div>Integrator Module</div> </div> <div> <div>DID4</div> <div>Adjustable Integrator Module</div> </div>	
APPLICATIONS	New Construction, Remodel, Retrofit	
HOUSINGS/FIXTURES	OneFrame, SquareFrame, SurfaceFrame, Classic Frames 4", 5", 6"	OneFrame, SquareFrame, Classic Frames 4", 5", 6"
DELIVERED LUMENS	750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14W)	750 lm (9.7W), 1000 lm (12W)
COLOR QUALITY	93+ CRI, 2-step SDCM	93+ CRI, 2-step SDCM
COLOR TEMPERATURES	<div> <div></div> 2700K <div></div> 3000K <div></div> 3500K <div></div> 4000K <div></div> Warm Dim (3000 - 1800K) </div>	
BEAM SPREAD	<div> <div></div> 15° Narrow Spot <div></div> 90°+ General Ambient </div> <div> <div></div> 25° Spot <div></div> 40° x 20° Linear Spread </div> <div> <div></div> 40° Flood <div></div> Soft Focus </div> <div> <div></div> 60° Wide Flood </div>	<div> <div></div> 15° Narrow Spot <div></div> 60° x 30° Linear Spread </div> <div> <div></div> 25° Spot <div></div> Soft Focus </div> <div> <div></div> 40° Flood </div>
SPECIALTY LENS	<div> <div></div> Hexcell Louver </div>	
ADJUSTMENTS	—	360° Directional Aim, 45° Tilt
INPUT VOLTAGE	120 / 277V	
1% DIMMING	TRIAC/ELV, Lutron EcoSystem	
ONEFRAME TRIMS	Round Beveled, Square, Hyperbolic, Pinhole, Beveled Pinhole, Wall Wash, Decorative, Flangeless, Dead Front	Round Beveled, Hyperbolic, Pinhole, Beveled Pinhole, Flangeless
SQUAREFRAME TRIMS	Square, Round on Square, Pinhole, Beveled Pinhole, Wall Wash, Decorative, Flangeless, Dead Front	Round on Square, Pinhole, Beveled Pinhole, Flangeless
CLASSIC TRIMS	4": Round Beveled, Round Baffle, Square, Wall Wash; 5": Round Beveled, Round Baffle, Wall Wash; 6": Round Beveled, Round Baffle, Wall Wash	4": Beveled, Baffle; 5": Beveled, Baffle; 6": Beveled, Baffle
TRIM FINISHES	<div> <div></div> White <div></div> Black <div></div> Silver <div>+</div> Custom </div>	
ONEFRAME/SQUAREFRAME RATINGS	<div> <div></div> Fire Rated <div></div> Sound Rated <div></div> IC Rated <div></div> Air Tight </div>	
MODULE RATINGS	<div> <div></div> Wet Location </div>	<div> <div></div> Damp Location </div>
STANDARDS	<div> <div></div> <div></div> <div></div> <div></div> </div>	
GUARANTEE	<div> <div></div> <div></div> </div>	